



DECO-CRETE 5000

Construction Grade Concrete Mix

PRODUCT DESCRIPTION

Deco-Crete 5000 is a single-component premium concrete bag mix designed for general-purpose and high-performance concrete repairs. Its "just add water" formula makes it easy to mix with no other additives required. Our specialized mix design sets quickly and trowels like ready-mix concrete, giving you a professional finish with minimal wait time. Deco-Crete 5000 can be applied 2" thick and up. The mix includes 3/8" gravel aggregate. Its high-strength composition provides long-lasting performance, making it ideal for both DIY enthusiasts and contractors.

TECHNICAL INFO

Coverage.....3 sq/ft at 2" thick
 2 sq/ft at 3" thick
 1.5 sq/ft at 4" thick

**Each 60 lbs. bag will yield approximately 0.45 cubic feet.*

Compressive Strength

3 Days.....3,580 psi
 7 Days.....3,940 psi
 28 Days.....5,890 psi
 Color.....Gray
 Packaging60 lbs. bag

RECOMENDED APPLICATIONS

- + Concrete Projects 2" Thick and Up
- + Concrete Repairs
- + Small Foundations and Footings
- + Post Anchoring



QUICK FACTS

- + Just Add Water
- + Sets and Finishes Like Ready-Mix Concrete
- + High-Strength
- + Interior or Exterior
- + Made In The USA



DECO-CRETE 5000

Construction Grade Concrete Mix

INSTRUCTIONS FOR USE

MIXING INSTRUCTIONS

A heavy-duty drill and mixing paddle or drum mixer is required for proper mixing. Always add the dry powder to water. Start 3.5 - 4 quarts of water in a suitable container. Add Deco-Crete 5000 and mix thoroughly for 2 minutes. Scrap the sides of the bucket with a margin trowel and then mix for an additional minute. The exact amount of water needed will vary depending on the desired slump and consistency. When using a hand drill, introduce dry powder slowly and vary the depth of the mixing paddle to reduce lumping and ensure consistency.

SURFACE PREP

Prepare any necessary forms or holes to be filled prior to mixing. When applying over old concrete, be sure the base concrete is clean and free of dust, dirt, oils, or paints that will inhibit bonding. The use of Deco-Crete Surebond is recommended where increased bond is desired.

APPLICATION INSTRUCTIONS

Placement - Pour into form work at a minimum of 2" thick. After pouring, level off the concrete with a straight edge and float with magnesium tools. As the Deco-Crete 5000 sets, concrete finishing tools may be used to obtain the desired finish. A mason's brush or broom pulled across the top after floating or troweling will provide a slip-resistant surface. Or use steel finishing trowels to smooth out the surface for a slick finish.

SEALING

Deco-Crete recommends sealing broomed finishes with D-Shield and most other finishes with D-One. Please refer to Deco-Crete.com for more information on concrete sealers.

* Deco-Crete Supply is not responsible for application methods, finishing techniques or any other variables that cannot guarantee the final appearance. Deco-Crete Supply recommends that a representative jobsite sample be made for each product used.



For tutorials & even more decorative concrete content, follow the QR code here for our YouTube channel or find us on social media

