

# EASY STRIP Form Releaser Specification Sheet

## 1. PRODUCT NAME

EASY STRIP Form Releaser

## 2. DISTRIBUTOR

Deco-Crete Supply  
133 North Kohler Rd.  
Orville, Ohio 44667  
330-682-5678

## 3. PRODUCT DESCRIPTION

**Basic Use:** Easy Strip Form Releaser permits removal of forms, formliners, pallets, etc. from hardened concrete. It:

- Helps minimize clean-up of forms and equipment
- Promotes easy form stripping
- Is non-staining when used properly
- Properly applied does not “kill” concrete surfaces
- Good on aluminum forms
- Does not cause efflorescence

**Limitations:** Not recommended for forms or formliners made from expanded polystyrene, SBR, or natural rubber or latexes made of these.

## 4. TECHNICAL DATA

Please see Tables.

## 5. APPLICATION

**Preparatory Work:** Form surfaces should be clean, dry, and free from contaminants. Apply Easy Strip just minutes before concrete is placed or up to 7 days before if treated surface is protected.

Apply with any type applicator or technique. Use a sprayer, roller, brush, or mop.

Too much release agent will cause bugholes concrete build-up, soft spots, staining, and an increased difficulty in stripping.

### TABLE OF PROPERTIES

Color	Dark Amber
Opacity	Clear
“Freeze” Temperature	-10°F
Freeze Damage	None
Flash Point	275°F
Viscosity (centipoises)	15 @ 68°F
Solids	None
Pounds per gallon	7.3
VOC	250 g/L

**Composition:** A proprietary blend of vegetable oils in petroleum based oils. Contains no silicones...no carcinogens.

Spraying problems (thickening of the form releaser) caused by temperatures below 50°F can be minimized by increasing spray pressure by about 10 psi. At lower temperatures it may be wise to use a larger spray tip...say 8005.

**Storage:** Factory sealed containers will keep up to 2 years at temperatures from -20°F to 140°F (-30°C to 60°C). Easy Strip is a class 3A liquid for purposes of meeting OSHA storage requirements (Section 1910.106).

**Precautions:** Keep out of reach of children. Avoid prolonged contact with the skin. Use with adequate ventilation. See Material Safety Data Sheet for additional information.

## 6. AVAILABILITY AND COST

**Availability:** Easy Strip is available in 1 and 5 gallon containers; 55 gallon drums and 275 gallon MegaPaks.

### COVERAGE WITH EASY STRIP

Form Surface	(sq ft/gal)
Hard & Smooth	1,000
Pre-oiled Plywood	600
Untreated Plywood	500

### TABLE OF FORM AND FORMLINER COMPATIBILITY

<b>Plywood</b>	All grades, Pre-oiled, Overlaid (LDO, MDO, HDO)
<b>Plastics</b>	Fiberglass reinforced, ABS, PVC
<b>Coatings</b>	Epoxy, Urethane
<b>Elastomerics</b>	Urethane, Silicone
<b>Steel</b>	
<b>Aluminum</b>	
<b>Wood</b>	

## **7. LIMITED WARRANTY**

Deco-Crete Supply warrants the product against defects in materials for a period of 1 year from purchase. If Deco-Crete Supply receives notice of such defects during the warranty period, Deco-Crete at its option will either replace the product or refund the purchase price. THE WARRANTY SET FORTH ABOVE IS EXCLUSIVE AND NO OTHER WARRANTY, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED. DECO-CRETE SUPPLY SPECIFICALLY DISCLAIMS THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES PROVIDED HEREIN ARE BUYER'S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL DECO-CRETE SUPPLY BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOSS OF PROFIT) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY.

## **8. MAINTENANCE**

Not required.