# SAFETY DATA SHEET

Issue Date 28-May-2015 Revision Date 28-May-2015 Version 1

### 1. IDENTIFICATION

Product identifier

Product Name Kolour Koat Acrylic Color Pack

Other means of identification

Product Code Synonyms

Recommended use of the chemical and restrictions on use

**Recommended Use** Pigment. **Uses advised against** No Data

Details of the supplier of the safety data sheet

**Distributor Address** 

Deco Crete Supply 133 North Kohler Road Orrville, OH 44667

Emergency telephone number

Company Phone Number (330) 682-5678

24 Hour Emergency Phone Number 800-535-5053 (United States & Canada), International Call: 1-352-323-3500

### 2. HAZARDS IDENTIFICATION

#### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids Category 3 Hazardous to the Aquatic Environmen	t - Acute Hazard Category 2

#### Label elements

### **Emergency Overview**

### Danger!

#### Hazard statements

Highly flammable

Suspected of Causing Cancer

Toxic to Aquatic Life with Long Lasting Effects

Causes Serious Eye Irritation

May Cause Respiratory Irritation

May Cause Drowsiness or Dizziness

May be Harmful if Swallowed

May be Harmful if Swallowed and Enters Airways

Causes Skin Irritation



**Appearance** Opaque Liquid

Physical state liquid

Odor Mild Petroleum Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/.?/equipment

Use only non-sparking tools

Take action to prevent static discharges

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Avoid release to the environment

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

If skin irritation occurs: Get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor

Do NOT induce vomiting.

Take off contaminated clothing and wash before reuse

In case of fire use, "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish.

Collect spillage

#### **Precautionary Statements - Storage**

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

### **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local/regional/national regulations.

#### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

### Other Information

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Non-hazardous ingredient(s)	-	60 - 100	*
Methoxyisopropyl acetate	108-65-6	10 - 30	*

Isobutyl Isobutyrate	97-85-8	5 - 10	*
Butyl acetate	123-86-4	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### Description of first aid measures

General advice Move out of the dangerous area. Consult a physician. Provide this Safety Data Sheet to the

doctor in attendance.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash off immediately with soap and plenty of water. If skin irritation

persists, call a physician.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If breathing is irregular or stopped, administer artificial respiration. If symptoms

persist, call a physician.

Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT

induce vomiting. Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

**Symptoms** Eye, Skin, and Respiratory Irritation.

### Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. For additional information, see Safety Data Sheet.

### 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Dry Chemical, Alcohol Resistant Foam, Halon or Carbon Dioxide.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

In a fire or if heated a pressure increase may occur and the container may burst.

Hazardous combustion products Carbon dioxide (CO2). Carbon monoxide.

### Explosion data

Sensitivity to Mechanical Impact Not available.

**Sensitivity to Static Discharge** May be ignited by friction, heat, sparks or flames.

#### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment as required. P261 - Avoid breathing

dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation, especially in confined areas.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not allow product to enter any drains

or waterways.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills.

Methods for cleaning up

Use a non-combustible material like vermiculite or sand to soak up the product and place

into a container for later disposal. Use clean non-sparking tools to collect absorbed

material. Dispose according to local regulations.

### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Do not handle until all safety precautions have been read and understood. Avoid contact

with skin and eyes. Avoidbreathing dust/fume/gas/mist/vapours/spray. Keep away from heat, hot surfaces, sparks, open flames and otherignition sources. No smoking. Ground and bond container and receiving equipment. Take measures to prevent thebuildup of electrostatic charge. Use non-sparking tools. Wash hands and skin thoroughly after handling. Use onlyoutdoors or in a well-ventilated area. Wear protective gloves/protective

clothing/eye protection/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Containers which are

opened must be carefully resealed and kept upright to prevent leakage.

**Incompatible materials** Keep away from strong oxidizing agents, strong alkalis, and strong acids.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Butyl Acetate - CAS 123-86-4: TWA 150ppm ACGIH, STEL 200ppm ACGIH, TWA 150ppm

OSHA PEL.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butyl acetate	STEL: 200 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 150 ppm	TWA: 710 mg/m <sup>3</sup>	TWA: 150 ppm
		(vacated) TWA: 150 ppm	TWA: 710 mg/m <sup>3</sup>
		(vacated) TWA: 710 mg/m <sup>3</sup>	STEL: 200 ppm
		(vacated) STEL: 200 ppm	STEL: 950 mg/m <sup>3</sup>
		(vacated) STEL: 950 mg/m <sup>3</sup>	· ·

#### **Appropriate engineering controls**

Engineering Controls General/Local Ventilation Recommended.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact. Wear chemical resistant gloves at minimum. Wash

skin immediately upon contact. Wash hands at mealtime and end of shift.

**Respiratory protection**Use respiratory protection unless adequate local exhaust ventilation is provided or

exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29)

Remarks • Method

CC (closed cup)

CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

and after breaks and at the end of the work day.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state liquid

AppearanceOpaque LiquidOdorMild Petroleum SolventColorVariousOdor thresholdNo data available

Valious Odol till esticid No data ava

Property
pH Values
Not Available

Melting point / freezing point

Boiling point / boiling range

Not Applicable
122 °C

Flash point < 37 °C (98 °F)

Evaporation rate Varies
Flammability (solid, gas) Not Relevant

Flammability Limit in Air

Upper flammability limit: 13.0% Lower flammability limit: 1.0%

Vapor pressure Not Available Vapor density Not Available

Relative density Varies @ 70 Degrees F
Water solubility Insoluble in water

Solubility in other solvents Not Available Partition coefficient Not Available **Autoignition temperature** Not Available **Decomposition temperature** Not Available Kinematic viscosity Not Available **Dynamic viscosity** Not Available **Explosive properties** Not Available Oxidizing properties Not Available

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
Bulk density
Not Relevant
Not Available
Not Applicable
Not Available
Not Available

## 10. STABILITY AND REACTIVITY

Reactivity

Not Available

**Chemical stability** 

Stable.

Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

**Conditions to avoid** 

Heat, flames and sparks.

**Incompatible materials** 

Keep away from strong oxidizing agents, strong alkalis, and strong acids.

### **Hazardous Decomposition Products**

Hazardous decomposition products formed under fire conditions, carbon oxides.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

Inhalation Direct contact and vapor inhalation.

Eye contact Direct contact.

Skin contact Direct contact.

Ingestion Direct contact.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methoxyisopropyl acetate 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
Isobutyl Isobutyrate 97-85-8	= 12800 mg/kg (Rat)	> 8600 mg/kg (Rabbit)	= 5000 ppm (Rat) 6 h
Butyl acetate 123-86-4	-	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat)4 h

### Information on toxicological effects

**Symptoms** May cause drowsiness or dizziness if inhaled. May cause respiratory irritation. Causes

serious eye irritation. Causes skin irritation.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe burns. Irritating to skin.

Serious eye damage/eye irritation Irritating to eyes. Risk of serious damage to eyes. Irritation Irritating to eyes, respiratory system and skin.

Sensitization No data available. Germ cell mutagenicity No data available. Carcinogenicity No Data Available. Reproductive toxicity Not Available. STOT - single exposure Not Available. STOT - repeated exposure Not Available. **Aspiration hazard** Not Available.

### Numerical measures of toxicity - Product Information

### 12. ECOLOGICAL INFORMATION

Material is expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### **Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methoxyisopropyl acetate 108-65-6	-	161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50
Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50

\_\_\_\_\_

### Persistence and degradability

No data available.

#### **Bioaccumulation**

No data available.

Chemical Name	Partition coefficient
Methoxyisopropyl acetate 108-65-6	0.43
Butyl acetate 123-86-4	1.81

Other adverse effects No data available.

### 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes Under RCRA 40 CFR 261 this material is a hazardous waste. Dispose of in accordance

with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area. Contact a

licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

Chemical Name	California Hazardous Waste Status
Butyl acetate	Toxic
123-86-4	

### 14. TRANSPORT INFORMATION

DOT UN1263, PAINT, 3, III

**Special Provisions** DOT Shipping Note: Consumer Commodity, ORM-D when inner contents are < 1 Liter.

(Ground)

Marine pollutant Material is expected to be harmful to aquatic organisms. May cause long-term adverse

effects in the aquatic environment.

IATA UN1263, PAINT, 3, III

IMDG UN1263, PAINT, 3, III

### 15. REGULATORY INFORMATION

International Inventories

TSCA Does not comply
DSL/NDSL Does not comply
EINECS/ELINCS Does not comply
ENCS Does not comply
IECSC Does not comply
KECL Does not comply
PICCS Does not comply

**AICS** Does not comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** Yes Fire hazard Yes Sudden release of pressure hazard Yes **Reactive Hazard** No

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate 123-86-4	5000 lb	-	-	Х

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl acetate	5000 lb	<del>-</del>	RQ 5000 lb final RQ
123-86-4			RQ 2270 kg final RQ

#### **US State Regulations**

### **California Proposition 65**

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

### U.S. State Right-to-Know Regulations

### U.S. EPA Label Information

### 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 1 **Physical and Chemical** Properties -

HMIS Health hazards 2 Flammability 3 Physical hazards 1 Personal protection -

**Issue Date** 28-May-2015 **Revision Date** 28-May-2015

**Revision Note** No data available **Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**