

DECO GRIP

40, 60 or 100 Grit Additive For Solvent Based Sealers

Product Description

Deco Grip is a micronized polymer specially designed for added grip, slight loss of gloss, and fine texturing in solvent based acrylic concrete coatings, paints, etc. Because of Deco Grip's high solvent resistance and very low oil absorption, it will stir into solvent based acrylic coatings easily without noticeably changing the sealers viscosity. Suspension is a key characteristic of Deco Grip due to its low density, even in very low viscosity coatings. Deco Grip comes in three sizes, 100 (the smallest particle size), 60 and 40.

Benefits & Features

- Provides superior slip resistance to a wide variety of coating applications
- This product can be added to not only solvent based acrylic coatings, but paints, epoxies, etc.
- Excellent suspension characteristics provide universal compatibility without a high viscosity increase

Technical Information

Solids/Active Content, Percentage by weight	0%
Solvent Resistance	Superior
Dry Time - Foot Traffic	N/A
Dry Time - Heavy Traffic	N/A
Recoat Time Window	N/A
VOC (Volatile Organic Compound) Content	0 grams/liter
Appearance	Clear sand

Specifications/Compliances

VOC and OTC complaint

Approximate Coverage Rates

Coverage rates vary depending upon amount used per gallon of coating. Note that no more than 6 ounces per gallon should be used.

Shelf Life

Deco Grip has a shelf life of more than two years in it's original, sealed, unopened container.

Packaging

Packaged in 16 oz plastic containers. Available in 40, 60 and 100 mesh.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.eco-cretesupply.com

Instructions for Use

Preparation: Substrate temperature must be no less than 40°F and not exceed 80°F. If applied outside these limits, the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing.

Mixing: Stir in desired amount of grit into coating for 2 - 3 minutes. Additional stirring may be required if coating is left unstirred for an extended period of time. Broadcasting the grit over freshly applied coatings is sufficient as well, however, test your broadcasting method prior to complete application so over application is avoided.

Application: It is recommended to roll any coating when grit is in addition. Be aware that grit may be trapped in sprayer components backing up the operational mechanisms if a sprayer is used for application.

Please note: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application.

Clean-up

Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

Precautions & Limitations

- Deco Grip will not freeze but should be stored in a moderately cool environment, not freezing.
- Deco Grip is an environmentally safe product that contains no hazardous fumes nor VOC's
- Test this product prior to use. Once applied into a coating, the coating must be stripped to remove the grit
- Usage rates depend upon the desired amount of grip of the surface
- Deco Grip was designed as a grip additive and not as a coating matting agent
- Deco Grip has minimal resistance to brake fluid, gasoline, and many similar products
- Use Deco Grip in conjunction with coatings only. It is not recommended to use it with raw solvents
- Deco Grip may change the desired look of the coating applied. Test prior to use.

Special Notes

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.deco-cretesupply.com